



For commercial and industrial Class A fires

Badger's water extinguisher is ideal for Class A fires involving common combustibles such as trash, fabrics, wood and paper. Water is economical and easy to clean up.

The Badger model WP-61 water fire extinguisher has additionally been UL tested and listed as a "Loaded Stream" fire extinguisher. When properly charged using the Badger AC-40 potassium acetate loaded stream charge (P/N 00792) this extinguisher is approved for low temperature applications down to -40°F (-40° C).

For specific recharge instructions, refer to the nameplate and service manual (P/N 24642).

The time proven design of the Badger WP-61 Water fire extinguisher makes it extremely effective, simple to use, inexpensive and easy to recharge.

Features:

- *Heavy-duty chrome plated brass valves*
- *Comfortable stainless steel handles and operating levers*
- *Large loop stainless steel pull pins with retention tether*
- *Hex valve collar tightening ring for easy recharge*
- *UL listed—Meets D.O.T. requirements*
- *Six year warranty*
- *Full stainless steel cylinder and base*
- *Easy-to-read two-piece nameplates*



Technical Data:

BADGER *Extra* Water Stored Pressure Extinguisher

MODEL	WP-61
PART NUMBER	16888
CAPACITY (gallon)	2.5
CAPACITY (liter)	9.46
UL FIRE RATING	2-A
AGENT TYPE	Water
CYLINDER MATERIAL	Stainless Steel
VALVE MATERIAL	Plated Brass
HANDLE/LEVER MATERIAL	Stainless Steel
EXPELLANT	Nitrogen/Air
Operating Pressure @ 70° F	100
TEMPERATURE RANGE (° F)	33 to 120
TEMPERATURE RANGE (° C)	0.6 to 48.9
AGENT FLOW RATE (lb/sec)	n/a
AGENT FLOW RATE (kg/sec)	n/a
NOM. DISCHARGE TIME (sec)	55
DISCHARGE RANGE (ft.)	30.0 to 45.0
DISCHARGE RANGE (m)	9.1 to 13.7
UNIT HEIGHT (in.)	24.75
UNIT HEIGHT (cm)	62.9
UNIT WIDTH (in.)	8.75
UNIT WIDTH (cm)	22.2
UNIT DEPTH (in.)	7
UNIT DEPTH (cm)	17.8
SHIPPING WEIGHT (lb.)	8
SHIPPING WEIGHT (kg)	3.6
USCG APPROVAL	n/a
BRACKET	UB-20 Optional

This information is subject to change without notice. Badger Fire Protection disclaims any liability for any errors or misinterpretations of the information contained therein. Contact Badger Fire Protection for your local distributor for assistance.

Distributed by:

Badger Fire Protection
944 Glenwood Station Lane, Suite 303
Charlottesville, VA 22901
Tel.: 434.964.3200 • Fax: 434.964.3202
www.badgerfire.com

SS B-009
All Rights Reserved.

May 2013

