



Product Information Sheet



WET CHEMICAL - CLASS K

6 Liter & 2.5 Gallon Stored Pressure Models



**MODEL SHOWN.
6 LITER WET CHEMICAL**

Wet Chemical Fire Extinguishers contain a blend of Potassium Acetate and Potassium Citrate that is extremely effective in combating fires fueled by the unsaturated cooking oils and greases used in today's commercial cooking appliances. This agent excels at effectively fighting and cooling these very hot and difficult fires and its sealing qualities prevent re-ignition.

The misting nozzle delivers the agent in a fine spray that prevents splashing of the burning grease and confines it to the cooking surface.

The extinguishers are manufactured, tested, and Listed to ANSI/UL 8 and ANSI/UL 711 Standards.

The extinguishers are designed to work in conjunction with pre-engineered kitchen fire suppression systems. They have been tested to extinguish one 18" x 24" fryer.

SPECIFICATIONS		
Model	WC-6 Liter	WC-2.5 Gallon
Part Number	50006	50025
UL Rating	1A:K	1A:K
Capacity (gal/Liter)	1.59 / 6	2.5 / 9.6
Operating Pressure	100 psi (690 kPa)	100 psi (690 kPa)
Discharge time (Seconds)	54	73
Temperature Range	+40°F to +120°F	+40°F to +120°F
Cylinder Construction	Stainless Steel	Stainless Steel
Shipping Weight (lbs/kg)	22 / 10	33 / 15
Extinguisher Height (in/cm)	19.25 / 48.9	24.5 / 62.2
Width w/ Hose Installed (in/cm)	9 / 22.9	9 / 22.9
Cylinder Diameter (in/cm)	7 / 17.8	7 / 17.8
Standard Mounting Hardware	Wall Hook	Wall Hook

